



# BAXI

Warmth, efficiency,  
and total peace of mind.

## Baxi GL (Glass Lined) Indirect Water Heater

- Easy to Install
- Low Pressure Drop
- Magnesium Anode Rod Corrosion Protection
- Enameled Coated Steel Tank and Coil
- Minimal Standby Losses
- Flexible Scratch Resistant Jacket
- Aquastat Sensor Well
- Temperature Pressure Relief Valve
- Residential Limited Warranty:  
Tank, 8-Years; Parts, 5-Years
- Commercial Limited Warranty:  
Tank, 5-Years; Parts, 2-Years



# Baxi GL (Glass Lined) Indirect Water Heater

Model	Sku #	Storage Volume (Gallons)	Coil Heating Surface (Square Feet)	Dimensions (Inches)		Piping Connections N.P.T.		Approx. Wgt. (lbs.)
				Height	Diameter	Domestic Water In/Out	Boiler Water In/Out	
H2O 40 GL	H2OIG40BX	42	14	45	24	1	1	180
H2O 50 GL	H2OIG50BX	53	14	51	24	1	1	200
H2O 80 GL	H2OIG80BX	79	20.7	48	30	1	1	243

Model	Sku #	Max. First Hour Rating Gal./Hr. @ 115° F	Continuous Rating Gal./Hr. @ 115° F	Boiler Output Needed (MBH)	Boiler Water Flow Through the Coil (Gal./Min.)	Pressure Drop Through the Coil (Ft. Water)
H2O 40 GL	H2OIG40BX	198	162	105	14.0	10.7
		256	220	120		
H2O 50 GL	H2OIG50BX	212	169	110	14.0	10.7
		310	268	140		
H2O 80 GL	H2OIG80BX	228	164	110	14.0	15.9
		346	281	180		



Note: All ratings are based on 170° F boiler water supply temperature. Domestic hot water 70° F rise, 45° F water inlet temperature. Specifications subject to change without notice.

Standard Equipment	Smooth enameled coil, magnesium anode rod and temperature pressure relief valve, Honeywell Aquastat. Water tank temperature gauge.
--------------------	--



www.baxiboilers.com



All specifications subject to change without notice.

©2019 Baxi N.A.

PN 240012463 Rev. [8/19/19]